



OMB5200 Series

432x348x132.6

(17"x 13.7"x 5.22")

OA300ST Series

432x203x44.5mm

(17"x 8"x 1.75")

| | |
|--|--|
| <p>FRONT</p>  <p>BACK</p>  <p>Unit slides in to any standard 19" rack.</p> <p>Tray features 2 high performance sealed ball bearing fans.</p> <p>Power cord configured for standard 115 VAC or 230 VAC connection</p> | <p>FRONT</p>  <p>BACK</p>  <p>Lighted rocker switch</p> <p>Resettable circuit breaker.</p> <p>Unit slides in to any standard 19" rack.</p> <p>Tray features 3 high performance sealed ball bearing fans.</p> <p>Black electro deposit finish for long life</p> |
|--|--|

| Part Number | OMB5200-120 | OMB5200-230 | OA300ST-120 | OA300ST-230 |
|------------------------|-------------------|-------------------|-----------------------|-----------------------|
| No. of Fans | 2 | 2 | 3 | 3 |
| Bearing System | Dual Ball Bearing | Dual Ball Bearing | Dual Ball Bearing | Dual Ball Bearing |
| Nominal Voltage (60Hz) | 115 VAC | 230 VAC | 115 VAC | 230 VAC |
| Input Power | 70 Watts | 70 Watts | 45 Watts | 45 Watts |
| Rated Speed (RPM) | 3500 | 3500 | 3000 | 3000 |
| Airflow (CFM) | 340 | 340 | 310 | 310 |
| Noise Level (dB) | 57 | 57 | 53 | 53 |
| Life Expectancy | 60,000 hrs (25C) | 60,000 hrs (25C) | 60,000 hrs (25C) | 60,000 hrs (25C) |
| Connection | 1.8M Power Cord | 1.8M Power Cord | 2M Modular Power Cord | 2M Modular Power Cord |