

## External 192V 2U Rackmount Battery Pack for select Tripp Lite UPS Systems (BP192V5RT2U)

MODEL NUMBER: BP192V5RT2U



### Highlights

- Extends the runtime of expandable 192V DC Tripp Lite UPS Systems
- Supports 2U rackmount installation; 4 post installation accessories included
- Options for 2 post rackmount available

### Package Includes

- BP192V5RT2U external battery pack
- Mounting hardware
- Warranty information
- Instruction manual

### Description

Tripp Lite's BP192V5RT2U rack external battery pack offers extended battery runtime when used in conjunction with compatible Tripp Lite UPS systems. Multi-use form factor supports configuration in rackmount or stacking applications using only 2 rack spaces (2U). Includes heavy-gauge cabling with high-current DC connectors for simple installation. COMPATIBLE UPS SYSTEMS - [SU5000RT4U](#), [SU6000RT4U](#), [SU8000RT4U](#), [SU5000RT4UHV](#), [SU5000RT4UTF](#), [SU6000RT4UHV](#), [SU6000RT4UHVG](#), [SU6000RT4UHVHW](#), [SU6000RT4UHVPM](#), [SU6000RT4UTFHW](#), [SU6000RT4UTF](#) and other Tripp Lite UPS systems that specify the use of this battery pack.

### Features

- Offers extended-run UPS operation when used in conjunction with compatible Tripp Lite UPS systems
- Supports stacking or rackmount installation using only 2 rack spaces (2U)
- Mounting accessories included for 4 post rackmount installation
- Optional [2POSTRMKITWM](#) enables installation in 2 post racks
- Includes heavy-gauge cabling with high-current DC connectors for simple installation
- COMPATIBLE UPS SYSTEMS - [SU5000RT4U](#), [SU6000RT4U](#), [SU8000RT4U](#), [SU5000RT4UHV](#), [SU5000RT4UTF](#), [SU6000RT4UHV](#), [SU6000RT4UHVG](#), [SU6000RT4UHVHW](#), [SU6000RT4UHVPM](#), [SU6000RT4UTFHW](#), [SU6000RT4UTF](#) and other Tripp Lite UPS systems that specify the use of this battery pack.
- NOTE: LIMIT OF 1 BP192V5RT2U PER UPS, SEE [BP192V12-3U](#) FOR MULTI-PACK COMPATIBILITY

## Specifications

INPUT	
UPS Input Cord Length (ft.)	3
UPS Input Cord Length (m)	0.9



BATTERY	
Expandable Battery Runtime	Includes a second input/output connector to daisy-chain multiple battery packs
DC System Voltage (VDC)	192
UPS Connection	Detachable cable with UPS specific DC connector (90 cm length)
Typical Battery Lifespan	4-6 years typical (North America)
Expandable Runtime	Yes
PHYSICAL	
Installation Form Factors Supported with Included Accessories	4 post 19 inch rackmount
Installation Form Factors Supported with Optional Accessories	2 post rackmount(2POSTRMKITWM)
Installation Form Factor Notes	Upright vertical tower configuration is not recommended for this model
Shipping Dimensions (hwd / in.)	9.76 x 26.38 x 28.35
Shipping Dimensions (hwd / cm)	24.8 x 12 x 12.9
Shipping Weight (lbs.)	108.6
Shipping Weight (kg)	49.3
Unit Dimensions (hwd / in.)	3.43 x 17.32 x 19.83
Unit Dimensions (hwd / cm)	8.7 x 44 x 50.4
Unit Weight (lbs.)	75.2
Unit Weight (kg)	34.11
Material of Construction	Black steel cabinet
External Battery Pack Form Factor	Rack
WARRANTY	
Product Warranty Period (U.S. & Canada)	2-year limited warranty
Product Warranty Period (International)	1-year limited warranty
Product Warranty Period (Mexico)	1-year limited warranty
Product Warranty Period (Puerto Rico)	1-year limited warranty
Optional Coverage	3 year, 5 year, next day and on-site warranty coverage available



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)