


## XLT2420

Single-Stage Thermoelectric Cooler  
RoHS EU Compliant

### TYPICAL PERFORMANCE VALUES

Hot Side Temperature (°C)	27°C	50°C
Δ Tmax (°C-dry N <sub>2</sub> ):	59	67
Qmax (watts):	52	57
I <sub>max</sub> (amps):	5.6	5.6
V <sub>max</sub> (vdc):	14.4	16.0
AC Resistance (ohms):	2.2	---

### MECHANICAL CHARACTERISTICS




### ORDERING OPTIONS

Model Number	Description
XLT2420-00L	Lapped Model
XLT2420-01L	Lapped Model with Leadwires
XLT2420-00LS	Lapped and Sealed Model
XLT2420-01LS	Lapped and Sealed Model with Leadwires

### AVAILABLE MODIFICATIONS

- Rated operating temperature of 125°C.
- Designed for temperature cycling applications.
- Capable of rapid heating and cooling rates.
- Porch configuration for high strength leadwire connection.
- RTV sealing option available.
- Lapped option available for multiple module applications.

ENVIRONMENT: ONE ATMOSPHERE DRY NITROGEN



For performance information in a vacuum or with hot side temperatures other than 27°C or 50°C, contact one of our Applications Engineers at 877-627-5691.

Installation

Recommended mounting method: Clamp with uniform pressure to a flat surface with thermal interface material. For additional information, please refer to our TEC Installation Guide.

Operation Cautions

For maximum reliability, storage and operation below 125°C in a non-condensing environment is recommended. To minimize thermal stress, use linear/proportional temperature control or a similar method rather than an ON/OFF method.

CONTACT US:

For customer support or general questions please contact a local office below or visit our website at [www.marlow.com](http://www.marlow.com).

Marlow Industries, Inc.  
 10451 Vista Park Road  
 Dallas Texas 75238-1645  
 214-340-4900 (tel)  
 214-341-5212 (fax)  
 877-627-5691 (tech support)  
[www.marlow.com](http://www.marlow.com)

Marlow Industries Europe GmbH  
 Brunnenweg 19-21  
 64331 Weiterstadt  
 Germany  
 Tel.: +49 (0) 6150 5439 - 403  
 Fax: +49 (0) 6150 5439 - 400  
[info@marlow-europe.eu](mailto:info@marlow-europe.eu)

II-VI Japan Inc.  
 WBG Marive East 17F  
 2-6 Nakase, Mihama-ku  
 Chiba-Shi, Chiba 261-7117  
 Japan  
 81 43 297 2693 (tel)  
 81 43 297 3003 (fax)  
[center@ii-vi.co.jp](mailto:center@ii-vi.co.jp)  
[www.ii-vi.co.jp](http://www.ii-vi.co.jp)

II-VI Singapore Pte., Ltd.  
 Blk. 5012, Techplace II  
 #04-07 & 05-07/12, Ang Mo Kio Ave. 5  
 Singapore 569876  
 (65) 6481 8215 (tel)  
 (65) 6481 8702 (fax)  
[info@ii-vi.com.sg](mailto:info@ii-vi.com.sg)  
[www.ii-vi.com.sg](http://www.ii-vi.com.sg)

Marlow Industries China, II-VI  
 Technologies Beijing  
 A subsidiary of II-VI Incorporated  
 Rm 202, 1# Lize 2nd Middle Road  
 Wangjing, Chaoyang District  
 Beijing 100102 China  
 010-64398226 ext 105 (tel)  
 010-64399315 (fax)  
[info@iivibj.com](mailto:info@iivibj.com)