

Article Number: 596-00817

CORRIENTE NOMINAL MÁXIMA
VOLTAJE NOMINAL MÁXIMO
VOLTAJE MÁXIMO DEL SISTEMA
CORRIENTE MÁXIMA DEL CIRCUITO
CORRIENTE MÁXIMA NOMINAL DEL
CONTROLADOR DE CARGA, SI FUE
INSTALADO

Description: Solar Label, Printable, Spanish, DC Module, 4.0" x 2.0",

PET, Red, 50/roll

Base Data		
	Local Order Number	596-00817
	Туре	DC2011S
	Color	Red (RD)
	Features and benefits	<ul> <li>Made with UV-stable inks and materials for durability and weather resistance.</li> <li>Polyester is resistant to chemicals and solvents and will remain legible in dirty environments.</li> <li>High abrasion and scuff resistance for high-performance labeling.</li> <li>Meets NEC &amp; IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.</li> </ul>
	Quantity Per	roll
	Product Description	HellermannTyton pre-printed Solar Rating labels are designed to meet the requirements of the National Electrical Code and the International Fire Code as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV-stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.
	Technical Description	Printable Solar Label, Spanish Version, DC Module Label, 4.0" X 2.0", Red
	Local Order Number 2	English Version: 596-00253
	Short Description	Solar Label, Printable, Spanish, DC Module, 4.0" x 2.0", PET, Red, 50/roll
Product Dimensions		
	Length L (Imperial)	4.0"
	Length L (Metric)	101.6mm
	Width W (Imperial)	4.0"
	Width W (Metric)	101.6mm
	Height H (Imperial)	2.0"
	Height H (Metric)	50.8mm
Material and Specifications		
	Material	Type 840/926, Polyester (PET), white (WH) UV stable w/ clear Polyester laminate

generated on: 4/29/2017

## 596-00817



Material and Specifications	Material Shortcut	840/926
	Adhesive	Acrylic
	Adhesive Operating Temperature	-40°F to +180°F (-40°C to +82°C)
	Halogenfree	Yes
	Operating Temperature	-40°F to +302°F (-40°C to +150°C)
	ROHS Compliant	Yes
	Certification/Specification	UL969
	UL Recognized (US)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	50
	Package Quantity (Metric)	50
	Customs Number(Schedule B)	3919102055
	Labels per Column	1
	Labels per Row	1

generated on: 4/29/2017