

150-77940

Article Number: 150-77940

Description: Fir Tree with Tie, 6.0" Long, Mounting Hole Diameter .26" - .28", Height .3", PA66HS, Black, 500/pkg



Base Data	
Local Order Number	150-77940
Type	T30RFT6
Color	Black (BK)
Features and benefits	<ul style="list-style-type: none"> <li>• Fir tree design can be used with a wide variety of applications.</li> <li>• Disc on the top of the fir tree covers the hole and minimizes the ingress of water and dirt.</li> <li>• Friction tab inside of fir tree allows tie to sit in mount without falling out prior to installation.</li> </ul>
Quantity Per	bag
Product Description	HellermannTyton's fir tree mounts provide a secure grip in a mounting hole and protect against dirt and other impurities. The mount can slide along the strap of the cable tie for proper orientation. The fir tree mounts are designed to provide a low insertion force and high extraction force. This mount is sold as an assembly with the cable tie.
Short Description	Fir Tree with Tie, 6.0" Long, Mounting Hole Diameter .26" - .28", Height .3", PA66HS, Black, 500/pkg
Product Dimensions	
Minimum Tensile Strength (Imperial)	30.0lbs
Minimum Tensile Strength (Metric)	135N
Length L (Imperial)	6.0"
Length L (Metric)	148mm
Length L2 (Imperial)	0.46"
Length L3 (imperial)	0.54"
Length L3 (metric)	13.8mm
Fixation Method	Fir Tree
Identification Plate Position	none
Length L2 (Metric)	11.6mm
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.14"

150-77940



Product Dimensions	Width W (Metric)	3.6mm
	Width W2 (Imperial)	0.4"
	Width W2 (Metric)	9.0mm
	Width W3 (Imperial)	0.2"
	Width W3 (Metric)	5.0mm
	Height H (Imperial)	0.04"
	Height H (Metric)	1.1mm
	Height H2 (Imperial)	0.3"
	Height H2 (Metric)	7.5mm
	Bundle Diameter Min. (Imperial)	0.06"
	Bundle Diameter Min. (Metric)	5.0mm
	Bundle Diameter Max. (Imperial)	1.4"
	Bundle Diameter Max. (Metric)	35.0mm
	Disc Diameter (Imperial)	0.63"
	Disc Diameter (Metric)	16.0mm
	Panel Thickness Max. (Imperial)	0.12"
	Panel Thickness Max. (Metric)	3.00mm
	Panel Thickness Min. (Imperial)	0.03"
	Panel Thickness Min. (Metric)	0.75mm
	Mounting Hole Diameter D (Imperial)	0.26 - 0.28"
Mounting Hole Diameter D (Metric)	6.4 - 7.1 mm	
Mounting Hole Diameter D Min. (Imperial)	0.252"	
Mounting Hole Diameter D Max. (Imperial)	0.28"	
Material and Specifications		
	Material	Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)
	Material Shortcut	PA66HIRHS
	Material Cable Tie	Polyamide 6.6 heat stabilized (PA66HS)
	Flammability	UL 94 HB
	Operating Temperature	-40°F to +221°F (-40°C to +105°C)
	ROHS Compliant	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	500
	Package Quantity (Metric)	500

150-77940



Logistic and Packaging	Customs Number(Schedule B)	3926909987
	Weight (Metric)	0.9kg