PD2 series

PSB series POD series PTU2 series

Refer to our website for product details.

CCS STU-3000 For quick access.





Strobe function available by assembling with Digital Control Unit PD2 series






Strobe Unit


STU-3000

Features

- Enables use of continuous lighting as strobe lighting.
- You can set strobe lighting time from 0.01 to 99.99 msec.
- External trigger signal provides ON/OFF control of power at the specified pulse width and strobe lighting of LED Lights.




Example system configuration



Specifications

Model name	STU-3000
Input connector	SMP-04V-BC (12 or 24 VDC)
	M3 terminal block 3P (trigger inputs, FG connection terminals)
Output connector	SMP-02V-BC (12 VDC)
	SMP-03V-BC (24 VDC)
	M3 jack (ON/OFF signal)
Trigger	Photocoupler input, 5 to 24 VDC, current 5 mA max.
	Pulse width of 20 μs or more and rising edge of 10 μs max.
ON/OFF signal	Connected with input jack on the PD2 Control Unit for light ON/OFF signal
	Center: Signal line, Sleeve: GND
Lighting time	0.01 to 99.99 ms
Lighting delay	10 µs max.
Accessories	ON/OFF signal and Control Unit connection cables
Weight	400 g max.
Connectable Control Units	PD2-1012/1024/3012/3024/5012/5024/3012-2/3024-2

Dimensions (mm)





for Loan

Inquire on our website here. http://www.ccs-grp.com/contact/