## 2N2918

# DUAL SILICON NPN TRANSISTOR



www.centralsemi.com

## **DESCRIPTION:**

The CENTRAL SEMICONDUCTOR 2N2918 is a Dual Silicon NPN Transistor utilizing two individual chips mounted in a hermetically sealed metal case designed for differential amplifier applications.

**MARKING: FULL PART NUMBER** 



|   | •                                 |        |         |       |
|---|-----------------------------------|--------|---------|-------|
| MAXIMUM RATINGS: (T <sub>A</sub> =25°C)             | SYMBOL                            |        |         | UNITS |
| Collector-Base Voltage                              | $V_{CBO}$                         |        | 45      | V     |
| Collector-Emitter Voltage                           | VCEO                              |        | 45      | V     |
| Emitter-Base Voltage                                | $V_{EBO}$                         |        | 6.0     | V     |
| Continuous Collector Current                        | IC                                |        | 30      | mA    |
| Power Dissipation (One Die)                         | $P_{D}$                           | ;      | 300     | mW    |
| Power Dissipation (Both Dice)                       | PD                                | :      | 500     | mW    |
| Power Dissipation (One Die, T <sub>C</sub> =25°C)   | $P_{D}$                           |        | 750     | mW    |
| Power Dissipation (Both Dice, T <sub>C</sub> =25°C) | PD                                |        | 1.5     | W     |
| Operating and Storage Junction Temperature          | T <sub>J</sub> , T <sub>stg</sub> | -65 1  | to +200 | °C    |
| ELECTRICAL CHARACTERISTICS: (TA=25°C                | unless otherwise r                | noted) |         |       |
| SYMBOL TEST CONDITIONS                              |                                   | MIN    | MAX     | UNITS |
| I <sub>CBO</sub> V <sub>CB</sub> =45V               |                                   |        | 10      | nA    |
| loco \/oc=5.0\/                                     |                                   |        | 2.0     | nΔ    |


| Operating and t           | otorage burietion remperature 1,                                       | stg             | 0 1200 | O     |
|---------------------------|--|-----------------|--------|-------|
| ELECTRICAL (              | CHARACTERISTICS: (T <sub>A</sub> =25°C unless o                        | therwise noted) |        |       |
| SYMBOL                    | TEST CONDITIONS  | MIN             | MAX    | UNITS |
| ICBO                      | V <sub>CB</sub> =45V   |                 | 10     | nA    |
| ICEO                      | V <sub>CE</sub> =5.0V  |                 | 2.0    | nA    |
| <sup>I</sup> EBO          | V <sub>EB</sub> =5.0V  |                 | 2.0    | nA    |
| BVCBO                     | I <sub>C</sub> =10μA   | 45              |        | V     |
| BVCEO                     | I <sub>C</sub> =10mA   | 45              |        | V     |
| BVEBO                     | I <sub>E</sub> =10μA   | 6.0             |        | V     |
| VCE(SAT)                  | I <sub>C</sub> =1.0mA, I <sub>B</sub> =0.1mA                           |                 | 0.35   | V     |
| VBE(ON)                   | V <sub>CE</sub> =5.0V, I <sub>C</sub> =100μA                           |                 | 0.70   | V     |
| h <sub>FE</sub>           | V <sub>CE</sub> =5.0V, I <sub>C</sub> =10μA                            | 150             | 600    |       |
| hFE                       | $V_{CE}=5.0V$ , $I_{C}=10\mu A$ , $T_{A}=-55^{\circ}C$                 | 30              |        |       |
| hFE                       | V <sub>CE</sub> =5.0V, I <sub>C</sub> =100μA                           | 225             |        |       |
| hFE                       | V <sub>CE</sub> =5.0V, I <sub>C</sub> =1.0mA                           | 300             |        |       |
| f <sub>T</sub>            | V <sub>CE</sub> =5.0V, I <sub>C</sub> =500μA, f=20MHz                  | 60              |        | MHz   |
| C <sub>ob</sub>           | V <sub>CB</sub> =5.0V, I <sub>E</sub> =0, f=140kHz                     |                 | 6.0    | pF    |
| NF                        | $V_{CE}$ =5.0V, $I_{C}$ =10μA, $R_{S}$ =10kΩ,                          |                 |        |       |
|                           | f=1.0kHz, BW=200Hz   |                 | 3.0    | dB    |
|                           | V <sub>CE</sub> =5.0V, I <sub>C</sub> =100μA                           | 0.8             | 1.0    |       |
| $ V_{BE1}-V_{BE2} $       | $V_{CE} = 5.0V, I_{C} = 10\mu A$                                       |                 | 10     | mV    |
| $ V_{BE1}-V_{BE2} $       | V <sub>CE</sub> =5.0V, I <sub>C</sub> =100μA                           |                 | 5.0    | mV    |
| $ V_{BE1}-V_{BE2} $       | V <sub>CE</sub> =5.0V, I <sub>C</sub> =1.0mA                           |                 | 10     | mV    |
| $\Delta(V_{BE1}-V_{BE2})$ | $V_{CE}$ =5.0V, $I_{C}$ =100 $\mu$ A, $T_{A}$ =-55 $^{\circ}$ C to +25 | 5°C             | 1.6    | mV    |
| $\Delta(V_{BE1}-V_{BE2})$ | $V_{CE}$ =5.0V, $I_{C}$ =100 $\mu$ A, $T_{A}$ =+25 $^{\circ}$ C to +12 | 25°C            | 2.0    | mV    |

## 2N2918

# DUAL SILICON NPN TRANSISTOR




## **TO-78 CASE - MECHANICAL OUTLINE**



| DIMENSIONS     |        |       |        |       |
|----------------|--------|-------|--------|-------|
|                | INCHES |       | MILLIM | ETERS |
| SYMBOL         | MIN    | MAX   | MIN    | MAX   |
| A (DIA)        | 0.335  | 0.370 | 8.51   | 9.40  |
| B (DIA)        | 0.305  | 0.335 | 7.75   | 8.51  |
| С              | 0.150  | 0.185 | 3.81   | 4.70  |
| D              | -      | 0.040 | -      | 1.02  |
| E              | 0.500  | •     | 12.70  | -     |
| F (DIA)        | 0.016  | 0.021 | 0.41   | 0.53  |
| G              | 0.2    | 200   | 5.     | 08    |
| Н              | 0.1    | 00    | 2.     | 54    |
| J              | 0.028  | 0.034 | 0.71   | 0.86  |
| K              | 0.029  | 0.045 | 0.74   | 1.14  |
| TO 70 (DEV) DA |        |       |        |       |

TO-78 (REV: R1)



MARKING: FULL PART NUMBER

### **OUTSTANDING SUPPORT AND SUPERIOR SERVICES**



#### PRODUCT SUPPORT

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- · Inventory bonding
- · Consolidated shipping options

- · Custom bar coding for shipments
- · Custom product packing

#### **DESIGNER SUPPORT/SERVICES**

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free quick ship samples (2<sup>nd</sup> day air)
- Online technical data and parametric search
- SPICE models
- · Custom electrical curves
- Environmental regulation compliance
- · Customer specific screening
- · Up-screening capabilities

- · Special wafer diffusions
- · PbSn plating options
- Package details
- · Application notes
- · Application and design sample kits
- · Custom product and package development

#### **CONTACT US**

#### Corporate Headquarters & Customer Support Team

Central Semiconductor Corp. 145 Adams Avenue Hauppauge, NY 11788 USA

Main Tel: (631) 435-1110 Main Fax: (631) 435-1824

Support Team Fax: (631) 435-3388

www.centralsemi.com

Worldwide Field Representatives:

www.centralsemi.com/wwreps

**Worldwide Distributors:** 

www.centralsemi.com/wwdistributors

For the latest version of Central Semiconductor's LIMITATIONS AND DAMAGES DISCLAIMER, which is part of Central's Standard Terms and Conditions of sale, visit: www.centralsemi.com/terms

(000)www.centralsemi.com



# Product End of Life Notification

| PDN ID:            | PDN01061 |
|--------------------|----------|
| Notification Date: | 1/17/17  |
| Last Buy Date:     | 7/17/17  |
| Last Shipment Date | 1/17/18  |

Summary: All transistors manufactured in the TO-78 package are discontinued and now classified as End of Life (EOL).

Although Central Semiconductor Corp. makes every effort to continue to produce devices that have been proclaimed EOL (End of Life) by various manufacturers, it is an accepted industry practice to discontinue certain devices when customer demand falls below a minimum level of sustainability. Accordingly, the following product(s) have been transitioned to End of Life status as part of Central's Product Management Process. Any replacement product will be noted below. The effective date for placing the last purchase order will be six(6) months from the date of this notice and twelve(12) months from the notice date for final shipments; this may be extended if inventory is available.

| Central Part Number | Replacement |
|---------------------|-------------|
| CEN876              | N/A         |
| CEN894              | N/A         |
| CEN895              | N/A         |
| CEN896              | N/A         |
| CEN911              | N/A         |
| CEN947              | N/A         |
| CEN955 W/DATA       | N/A         |
| MD2219A             | N/A         |
| MD2369              | N/A         |
| MD2369A             | N/A         |
| MD2369B             | N/A         |
| MD2905              | N/A         |
| MD2905A             | N/A         |
| MD5179              | N/A         |
| MD7000              | N/A         |
| MD7001              | N/A         |
| MD7003              | N/A         |
| MD7003A             | N/A         |
| MD7003B             | N/A         |
| MD8002              | N/A         |
| MD8003              | N/A         |
| MD918               | N/A         |
| MD918A              | N/A         |
| MD918B              | N/A         |
| MD984               | N/A         |
| 2N2060              | N/A         |
| 2N2060A             | N/A         |
| 2N2060M             | N/A         |
| 2N2223              | N/A         |
| 2N2223A             | N/A         |
| 2N2453              | N/A         |
| 2N2453A             | N/A         |
| 2N2480              | N/A         |
| 2N2480A             | N/A         |
| 2N2639              | N/A         |
| 2N2640              | N/A         |
| 2N2641              | N/A         |
| 2N2642              | N/A         |
| *** CONTINUED ***   |             |
|                     |             |

DISCLAIMER: This End of Life (EOL) notification is in accordance with JEDEC standard JESD48 - Product Discontinuance. Central Semiconductor Corp. will make every effort to offer life-time buy (LTB) opportunities and/or offer replacement devices to existing customers for discontinued devices, however, one or both may not be possible for all devices. Please contact your local Central Semiconductor sales representative for LTB opportunities/additional information.

CCC785 REV 002



# Product End of Life Notification

| PDN ID:            | PDN01061 |
|--------------------|----------|
| Notification Date: | 1/17/17  |
| Last Buy Date:     | 7/17/17  |
| Last Shipment Date | 1/17/18  |

\*\*\* CONTINUED FROM PRIOR PAGE \*\*\*

| C . ID . N I        | <b>D</b> 1  |
|---------------------|-------------|
| Central Part Number | Replacement |
| 2N2643              | N/A         |
| 2N2644              | N/A         |
| 2N2652              | N/A         |
| 2N2652A             | N/A         |
| 2N2720              | N/A         |
| 2N2721              | N/A         |
| 2N2722              | N/A         |
| 2N2903              | N/A         |
| 2N2903A             | N/A         |
| 2N2913              | N/A         |
| 2N2914              | N/A         |
| 2N2915              | N/A         |
| 2N2915A             | N/A         |
| 2N2916              | N/A         |
| 2N2916A             | N/A         |
| 2N2917              | N/A         |
| 2N2918              | N/A         |
| 2N2919              | N/A         |
| 2N2919A             | N/A         |
| 2N2920              | N/A         |
| 2N2920A             | N/A         |
| 2N3726              | N/A         |
| 2N3727              | N/A         |
| 2N3806              | N/A         |
| 2N3807              | N/A         |
| 2N3808              | N/A         |
| 2N3809              | N/A         |
| 2N3810              | N/A         |
| 2N3810A             | N/A         |
| 2N3811              | N/A         |
| 2N3811A             | N/A         |
| 2N4015              | N/A         |
| 2N4016              | N/A         |
| 2N4854              | N/A         |
| 2N4937              | N/A         |
| 2N4938              | N/A         |
| 2N4939              | N/A         |
| 2N5793              | N/A         |
| 2N5794              | N/A         |
| 2N5796              | N/A         |
| 2N5912              | N/A         |
| 2N6502              | N/A         |
|                     |             |

\*\*\* CONTINUED \*\*\*

DISCLAIMER: This End of Life (EOL) notification is in accordance with JEDEC standard JESD48 - Product Discontinuance. Central Semiconductor Corp. will make every effort to offer life-time buy (LTB) opportunities and/or offer replacement devices to existing customers for discontinued devices, however, one or both may not be possible for all devices. Please contact your local Central Semiconductor sales representative for LTB opportunities/additional information.

CCC785 REV 002



# Product End of Life Notification

| PDN ID:            | PDN01061 |
|--------------------|----------|
| Notification Date: | 1/17/17  |
| Last Buy Date:     | 7/17/17  |
| Last Shipment Date | 1/17/18  |

\*\*\* CONTINUED FROM PRIOR PAGE \*\*\*

| Central Part Number                 | Replacement   |
|-------------------------------------|---|
| Central would be happy to assist yo | ou by providing additional information or technical data to help locate an alternate source if we |
| have no replacement available. Plea | ase email your requests to engineering@centralsemi.com.   |

DISCLAIMER: This End of Life (EOL) notification is in accordance with JEDEC standard JESD48 - Product Discontinuance. Central Semiconductor Corp. will make every effort to offer life-time buy (LTB) opportunities and/or offer replacement devices to existing customers for discontinued devices, however, one or both may not be possible for all devices. Please contact your local Central Semiconductor sales representative for LTB opportunities/additional information.

CCC785 REV 002