



TRū offers an easy-to-integrate, *projected capacitive multi-touch* experience consumers have come to expect. Perfect to use for your next innovative design project or installation.

- Quality multi-touch user experience
- Sophisticated bezel-free industrial design
- Portrait or landscape orientation
- Superior touch screen glass durability

## TRū 32" Multi-Touch Monitor

### Easy To Deploy

Plug-and-play ready monitor. Universal power connection adapts to 100 - 240V AC @ 50/60 Hz.

### Sophisticated Bezel-Free Design

Smooth touch surface across the entire face of the monitor for refined aesthetics and easy cleanability.

### High Definition

TRū 32" monitors offer full HD 1920 x 1080 resolution

### Effortless Multi-Touch Experience

Projected capacitive touch technology provides a smooth, effortless multi-touch experience – identical to many of your favorite mobile touch devices.

### Expanded Gesture Capability

Additional gesture software development tools and support are available to expand multi-touch functionality.

### Greater Durability

Optically bonded cover glass provides a highly durable surface for longer, trouble-free service life.

### Installation Flexibility

VESA mount, side mounting holes with brackets or an optional, heavy-duty stand gives you a choice of fixed or desktop mounting

### Windows 7 Certified



TRū projected capacitive monitors are certified to be compatible with Windows 7 by Microsoft.

## 32" Monitor Specifications



<b>DESKTOP MODEL</b>	<b>K32A-0111</b>
LCD Size / Type	32" TFT
Net Weight – Approximate	48 lb
Power Supply	100 – 240V AC
Power Consumption – Typical	100W
Aspect Ratio	16:9
Pixel Pitch	0.51075 H x 0.51075 V mm
Panel Resolution – Maximum	1920 x 1080
Display Colors	16.7 m
Contrast Ratio	5000:1
Brightness – Typical	360 cd/m <sup>2</sup>
Response Time – Typical	6.5 ms
Horizontal Viewing Angle – Typical	178°
Vertical Viewing Angle – Typical	178°
Video Signal Input	D-sub 15 pin Female Analog, DVI-D
Audio	3W, 2 Channel, Speaker 5W/8ohm
VESA Pattern	400 x 200 mm

### COMMON SPECIFICATIONS

<b>Multi-Touch OS Support</b>	Windows 7	<b>Single-Touch OS Support</b>	All Windows, Mac OS X, Linux – Certain Platforms
<b>Multi-Touch Input</b>	At least 2 unambiguous points	<b>Maximum Report Rate</b>	75 points per second
<b>Touch Technology</b>	Projected Capacitive	<b>Compliance</b>	TUV, CE, UL, CUL, FCC-B, RoHS, IPX1
<b>Touch Interface</b>	USB-Type B	<b>Mounting Options</b>	Edge Brackets, VESA Pattern or Optionals Stand

### OPERATING CONDITIONS

<b>Temperature</b>	0°C ~ +40°C
<b>Humidity</b>	20% ~ 80% Noncondensing

### STORAGE CONDITIONS

<b>Temperatures</b>	-20°C ~ +60°C
<b>Humidity</b>	10% ~ 90% Noncondensing