

111-05230

Article Number: 111-05230

Description: Standard Cable Tie, 12" Long, 50lb Tensile Strength, PA66, Natural, 1000/pkg



Base Data	Local Order Number	T50I9M4
	Type	T50I
	Color	Natural (NA)
	Features and benefits	<ul style="list-style-type: none"> • Inside serrations allow for strong hold on cables and wire bundles. • Head design provides high tensile strength with very low insertion force. • Bent tail ensures a quick and simple installation.
	Quantity Per	bag
	Product Description	HellermannTyton standard cable ties feature inside serrations to provide a positive hold onto wire and cable bundles. The head design guarantees high tensile strength, as well as a low insertion force. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.
	Short Description	Standard Cable Tie, 12" Long, 50lb Tensile Strength, PA66, Natural, 1000/pkg
	Product Dimensions	Minimum Tensile Strength (Imperial)
Minimum Tensile Strength (Metric)		225.0N
Length L (Imperial)		12.0"
Length L (Metric)		305.0mm
Fixation Method		None
Identification Plate Position		none
Releasable Closure		No
Tie Closure		plastic pawl
Variant		Inside Serrated
Width W (Imperial)		0.18"
Width W (Metric)		4.572mm
Bundle Diameter Min. (Imperial)		0.06"
Bundle Diameter Min. (Metric)		1.5mm
Bundle Diameter Max. (Imperial)		3.2"

111-05230



Product Dimensions	Bundle Diameter Max. (Metric)	80.0mm
	Thickness T (Metric)	1.2mm
Material and Specifications		
	Material	Polyamide 6.6 (PA66)
	Material Shortcut	PA66
	US MILSPEC	MS3367-5-9
	Flammability	UL 94 V2
	Halogenfree	Yes
	Operating Temperature	-40°F to +185°F (-40°C to +85°C)
	ROHS Compliant	Yes
	Certification/Specification	SAE - AS33671
	UL Listed (US and Canada)	Yes
	UL Recognized (US and Canada)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	1000
	Package Quantity (Metric)	1000
	Customs Number(Schedule B)	3926909987