| Mallory Sonalert Products, Inc. | | | | Part #: JT028-RYG-CS | |
|---------------------------------|----------------------|--------------------|---------------------|-------------------------------------------------------------------------------|---------------------------------------------|
| Sales Outline Drawing | | | | Revision: B | |
| Specifications: | | | | | |
| Stack Number: | 1 | 2 | 3 | | |
| LED Color: | RED | YELLOW | GREEN | | |
| Connection Wires: | Red and Brown | Yellow and Brown | Green and Brown | | |
| LED Current Draw: | <50mA | <60mA | <40mA | | • |
| Rated Voltage: | | | 24 VAC/DC | | |
| Operating Voltage: | 20-28 VAC/DC | | | | |
| Total Max Current: | <150mA | | | | |
| Operating Temperature: | -25° ~ +60°C | | | | |
| Lens Color: | Opaque White | | | | |
| Material: | ABS FR15U | | | | |
| Mounting Method: | Stainless Steel Pole | | | | |
| Weight Typical (g): | 625 | | | | |
| NEMA 12: | Approved | | | | |
| Options: | | cUL Recognized | Please contact fact | tory. | ROHS Compliant |
| 2.7 [68.3] TOP VIEW | ELLOW 2.4 [61.8] | OR WIRE TO POWER A | - - - | Ø0.20 [Ø5.2] 3 places 10 or 5mm rews for mounting 0.95 [24.3] MDUNTIN DIAGRAM | 48" wire ### ### ### ### ### ### ### |
| | | | | | |